

CONSPICUITY TAPE (10-YEAR)

PRODUCT INFORMATION GUIDE

Application(s): Our 7-year reflective sheeting is a high quality, durable, self-adhesive. Prismatic lens, retroreflective material. It is designed for use on vehicles for easy nighttime vehicle recognition. Meets DOT-C2 specification.

Adhesive: Permanent, Acrylic Pressure Sensitive Adhesive

Face Film: Vinyl Based Prismatic Reflective Film

Liner: Polymeric Film

Tape Application: Minimum application temperature 16^oC (60^oF)
Recommended for flat application to painted metal surfaces only. This product is not intended for application to stainless steel. Reflective sheeting is not designed for use as a printed decal. Applications involving the printing of this product are not covered by warranty. Surface must be free and clear of contamination.

Shelf Life: One year, when stored at 73^oF (23^oC), 50% +/- 5% relative humidity.

Property:	Test Method:	Measurement:
Outdoor Durability Operational Temp. Typical Film Caliper Specifications		10 years when properly processed and applied (vertical) (-23 ^o C to 72 ^o C) -10 ^o F to 160 ^o F 13.0 mils Meets or exceeds applicable requirements mentioned in NHTSA amendment FMVSS #108 (49 CFR 571) and carries "DOT-C2" certification.
Minimum Reflectivity Level * (per FMVSS 108, NHTSA & USDOT)		
Observation Angle (°)	Entrance Angle (°)	White Sheeting (Red Sheeting) (* CPL tested per ASTM E-810)
0.2	-4	250 (65)
0.2	30	250 (65)
0.2	45	60 (15)
0.5	-4	65 (15)
0.5	30	65 (15)
0.5	45	15 (4)
Typical Reflectivity Level *		
Observation Angle (°)	Entrance Angle (°)	White Sheeting (Red Sheeting) (* CPL tested per ASTM E-810)
0.2	-4	750 (170)
0.2	30	500 (110)
0.2	45	310 (70)
0.5	-4	230 (52)
0.5	30	120 (26)
0.5	45	82 (18)