

DUCT TAPE (DT398)

PRODUCT INFORMATION GUIDE

Application(s):	Premium grade duct tape for HVAC and general purpose applications. Versatile polyethylene coated cloth tape, that conforms well to irregular surfaces. High quality maintenance tape for a variety of manufacturing environments, asbestos removal and PE hanging. Tears Straight, and hangs straight.
Specifications:	Tested in accordance with UL 723
Comparable:	3M 6969, Cantech 99-21, Intertape AC36
Adhesive:	Natural Rubber Based Adhesive
Thickness:	11.0 MIL
Shelf Life:	One year from date of purchase when stored at 70 ⁰ F, 50% relative humidity.

Property:	Test Method:	Measurement:
Thickness	ASTM D-1000	11.0 MIL (0.28mm)
Adhesion to Steel	PSTC-1	47 oz/inch (52.6g/mm)
Adhesion to Backing	PSTC-1	46 oz/inch (51.5g/mm)
Tensile Strength	PSTC-1	27 lb/inch (0.483 kg/mm)
Unwind Force	ASTM D-1000	3.9lb/inch (69.9 g/mm)
Flame Spread		10
Smoke Spread		10
Max Temperature		200 ⁰ F



This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

Januray 2007.