

FLOW ARROW TAPE

PRODUCT INFORMATION GUIDE

Application(s):	Our directional flow arrows make a great choice for marking flow direction in virtually any pipe or vessel. The tape is made from full synthetic construction for water-proofness and durability. All printed images are continuous print without seam lines for a professional looking job. Tape has a removable liner.
Face Stock:	3.0 MIL polyethylene with 1.0 MIL biaxially-oriented polypropylene lamination
Total Thickness:	4.0 MIL
Adhesive:	Hot Melt Extra Permanent Rubber
Surface Application:	Minimum application temperature 10 ⁰ F Operational temperature -50 ⁰ F to 120 ⁰ F Surface must be clean and free from dust, dirt, oil, wax, silicone.
Shelf Life:	One year when stored at 72 ⁰ F at 50% RH

Property:	Test Method:	Measurement:
Face Stock		
Caliper	(mils)	4.0 MIL
Opacity	(%)	64
Tensile	(MD/TD)(lbs./sq.in)	34 / 26
Tear	(MD/CD)	37 / 37 grams
Adhesive		
Coat weight		14 lbs/3,300 Ft ²
Shear (1000g)	(Minutes)	140
90 Degree Peel	Stainless Steel	55 oz/inch (10 min. Dwell-Room Temp.)
Loop Tack	Stainless Steel	110 oz/inch (10 min. Dwell-Room Temp.)



This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.