

# HAZARD TAPE - LAMINATED

## PRODUCT INFORMATION GUIDE

<b>Application(s):</b>	Our general purpose PVC tape products are a great choice for floor aisle marking and color-coding pipe banding applications. Tape is overlaminated with a clear SPVC laminated for excellent durability. The 8 MIL PVC tape is formulated with a cross linked rubber adhesive providing good adhesive tack and flow, making it a good choice for most industrial applications.
<b>Adhesive:</b>	Crosslinked Rubber Adhesive
<b>Carrier:</b>	SPVC Vinyl (8 mil)
<b>Liner:</b>	No Liner - Tape Is Self Wound
<b>Shelf Life:</b>	One year from date of purchase when stored at 70 <sup>0</sup> F, 50% relative humidity.
<b>Safety Note:</b>	Laminated tape products have a smooth slick surface that will become particularly slippery when wet. Please take this into consideration when choosing this product for your intended application.

Property:	Test Method:	Measurement:
<b>PVC Film</b> Thickness Tensile Strength Elongation	PSTC-33 ASTM-D638 ASTM-D638	8 mils > 33 lb / inch > 200%
<b>Rubber Adhesive</b> Adhesion To Steel Adhesion To Backing Operational Temp. Min Application Temp.	ASTM D-1000 ASTM D-1000	22 oz/inch 22 oz/inch (-10 to 60 <sup>0</sup> C) -14 to 140 <sup>0</sup> F 10 <sup>0</sup> C (50 <sup>0</sup> F)

**INCOM**  
MANUFACTURING GROUP  
www.incomdirect.com

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

December 2006.