

PTK34 - POLYETHYLENE TAPE

PRODUCT INFORMATION GUIDE

Part Number: PTK34

Trade Names: Preservation Tape - Low Residue Removal Tape

Application(s): PTK34 is well suited for temporary applications with moderate levels of UV exposure that require a pressure-sensitive tape with excellent adhesion and conformability. Our Polyethylene tape is a heavy-duty conformable tape product suitable for most any patching, repair and bundling application. Great for surface protection, polyethylene splicing and wire identification. Permanently tacking adhesive bonds well to most surfaces over a wide temperature range. Excellent low temperature bonding. Product is very conformable. Maintains a water tight seal in all weather conditions. Good tear characteristics. Available in the following stock colors: clear, and silver. Also available in the following custom colors: silver, blue, black, burgundy, orange, yellow, green, teal, plum, and navy blue.

Adhesive: 2.5 mil (0.064mm) UV Stabilized Synthetic Rubber Adhesive (Low Residue)

Carrier: Polyethylene (4.5 mils)

Total Thickness: 7.0 mils (0.178mm)

Property:	Test Method:	Measurement:
Thickness	PSTC-33	7.0 mils (0.178mm)
Tensile Strength MD	ASTM-D1000	18 lbs/inch (79 N / 25mm)
Elongation	ASTM-D1000	100%
Peel Adhesion	PSTC 1 Mod	60 oz/inch (17 N / 25mm) Adhesion To Steel
Backing Adhesion	PSTC 1 Mod	35 oz/inch (10 N / 25mm) Adhesion To Backing

INCOM
MANUFACTURING GROUP
www.incomdirect.com

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

June 2010.