

# PTK36 - POLYETHYLENE TAPE

## PRODUCT INFORMATION GUIDE

**Part Number:** PTK36

**Application(s):** Our Polyethylene tape is a heavy-duty conformable tape product suitable for most any patching, repair and bundling application. Great for surface protection, polyethylene splicing and wire identification. Permanently tacking adhesive bonds well to most surfaces over a wide temperature range. Excellent low temperature bonding. Product is very conformable. Maintains a water tight seal in all weather conditions. Good tear characteristics. Available in the following stock colors: clear, silver, blue and black. Also available in the following custom colors: burgundy, orange, yellow, green, teal, plum, and navy blue.

**Adhesive:** 3.5 mils (0.089mm) Synthetic Rubber Adhesive - Clear

**Carrier:** Polyethylene (5.5 mils)

**Total Thickness:** 9.0 mils ( 0.229mm )

Property:	Test Method:	Measurement:
Thickness	PSTC-33	6.0 mils
Tensile Strength MD	ASTM-D1000	20 lbs/inch (88N / 25mm)
Elongation	ASTM-D1000	100%
Coating Thickness	PSTC-33	3.0 mils
Peel Adhesion	PSTC 1 Mod	70 oz/inch (19 N / 25mm) Adhesion To Steel
Backing Adhesion	PSTC 1 Mod	35 oz/inch (9.6 N / 25mm) Adhesion To Backing

**INCOM**  
MANUFACTURING GROUP  
[www.incomdirect.com](http://www.incomdirect.com)

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

June 2010.