

PREMIUM RESILIENT TAPE

PRODUCT INFORMATION GUIDE

Application(s):	Our premium resilient tape is a calendered vinyl film with moderate tensile strength, high elongation and good tear strength. This product is recommended for use on any clean dry surface to improve traction under both wet and dry conditions. An excellent choice for bare foot or office environments. Product available in 2 standard colors: Black and Gray. Custom colors also available.
Part Number:	PFX-Series
Adhesive:	Acrylic Adhesive
Carrier:	Vinyl film is calendered and embossed.
Liner:	Poly coated two sides, heavy weight 50g/inch release one side.
Thickness:	0.024" +/- 3%
Tape Application:	Minimum application temperature 10 ⁰ C (50 ⁰ F) Surface must be clean and free from dust, dirt, oil, wax, silicone.
Cleaning:	Clean substrate with a mild soap solution and water, rinse with fresh water.
Shelf Life:	One year from date of purchase when stored at 70 ⁰ F, 50% relative humidity.

Property:	Test Method:	Measurement:
PVC Film Thickness		0.024" +/- 3%
Acrylic Adhesive Dry Coat Weight		1.50 mils +/- 10%
Adhesion (Steel)	PSTC-1	43 oz./ inch (immediate) 53 oz./inch (24 hours) 78 oz./inch (7 days)

INCOM
MANUFACTURING GROUP
www.incomdirect.com

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

August 2006.