

# VINYL TAPE - CONFORMABLE

## PRODUCT INFORMATION GUIDE

<b>Application(s):</b>	Our general purpose PVC tape products are a great choice for floor aisle marking and color-coding pipe banding applications. The coloring is throughout the vinyl so it can not scratch or scuff during wear. The 6 MIL PVC film is formulated with a cross linked rubber adhesive providing good adhesive tack and flow, making it a good choice for most industrial applications.
<b>Adhesive:</b>	Crosslinked Rubber Adhesive
<b>Carrier:</b>	Vinyl (6 MIL)
<b>Total Thickness:</b>	6.8 MIL
<b>Specifications:</b>	Meets Federal Specification: PPP-T-66E
<b>Liner:</b>	No Liner - Tape Is Self Wound
<b>Shelf Life:</b>	One year from date of purchase when stored at 70 <sup>0</sup> F, 50% relative humidity.

Property:	Test Method:	Measurement:
<b>PVC Film</b>		
Thickness	PSTC-33	6 mils
Tensile Strength	ASTM-D638	> 15 lb / inch
Elongation	ASTM-D638	> 150%
<b>Rubber Adhesive</b>		
Dry Coat Weight	PSTC-33	35 g/m <sup>2</sup> (0.066 oz/yd <sup>2</sup> )
180 Peel Adhesion	PSTC-1	> 1 lb / inch
Operational Temp.		(-10 to 60 <sup>0</sup> C) -14 to 140 <sup>0</sup> F
Min Application Temp.		10 <sup>0</sup> C (50 <sup>0</sup> F)

**INCOM**  
MANUFACTURING GROUP  
www.incomdirect.com

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

November 2003.