

# Technical Data Sheet



## PVC Conformable Tape (PST, WT and VHT Series)

Issue Date: Oct/01/2015

### DESCRIPTION

Soft PVC tape suitably plasticized and stabilized. Coated with rubber-based pressure sensitive adhesive on one side. Matte finish industry tape.

### APPLICATION

For industrial identification, color coding and duct wrapping purpose.

### FEATURES/BENEFITS

- Suitable for uses under 60°C (140°F).
- It is moisture resistant, anti-corrosive and exhibits good adhesion to metal and plastic.
- Non-corrosive, pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts to affect application.
- No known hazards.

### TECHNICAL PERFORMANCE

Description	Units	Value	Test Method
Tape thickness	mm/mils	0.130/5.1	ASTM D-1000
Adhesion to steel	kg/cm, oz/in	0.16/14.11	ASTM D-1000
Elongation at break	%	150	ASTM D-1000
Tensile strength	kg/cm, lbs/in	2.0/11	ASTM D-1000

### STORAGE DETAILS

Shelf life recommended one year from the date of shipment when stored at 21°C (70°F) and 50% R.H.

### WARRANTY

The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy or suitability of information in this document to any specific applications. INCOM warrants its products to be free from defects but limits its obligation to replacement of products that have been proven, to INCOM's satisfaction, to be defective. This warranty is non-transferable and only applies to customers buying directly from INCOM. INCOM is not liable for any loss, damage, expenses, or consequential damages arising in connection with the use of this product.

**⚠ WARNING:** This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).